

# ROGUE<sup>XP</sup>



# ROGUE<sup>XP</sup>

You're **Young**. You're **Active**. You're **You**.

Engineered to meet the expectations of young riders, Rogue XP delivers unmatched performance, style, and adjustability. Designed for that age when individuality and built-in growth are non-negotiable. With no compromises on fit, function, ride, or style, Rogue XP empowers young riders to confidently navigate their world.



## Innovative Tower Design

Simplify Adjustments, Enhance Performance, and Save Time

- The **indexed rear seat height adjustment** offers up to 1.5" of rear seat height adjustment without disassembly to accommodate changes in ability, growth and seating.
- The patented **Dimple Track** provides guidance and alignment when adjusting center of gravity.
- Towers do not extend below the camber tube resulting in effortless vehicle loading and added storage space.

## Advanced Wing Design

Easier Reach, Smoother Transfers, Exceptional Stability

- Each frame is engineered with smart design calculations ensuring the wing is optimally positioned based on the chair's specifications.
- Internal, corrosion-resistant components protect against the elements, while the intuitive **Caster Angle Adjustment System** effortlessly adjusts without disassembly, for perfectly square casters at any seat angle.

[Learn More](#)



## Creative Expression



## Create A Look That Is Authentically You

Designed specifically for young riders, the **Rogue XP** offers more personalization options than any other chair in its class, with a wide selection of frame and wheel colors and customizable accents. Finished with an ultra-durable powder coat to ensure a vibrant appearance that stands the test of time.

## Specifications

\* 14"x14" frame, no armrests, without wheels

Transport Weight*	Seat Width	Seat Depth	Front Seat Height	Rear Seat Height	Camber
11.4 lbs.   5.2 kg	10-18"   25-46 cm	10-20"   25-51 cm	13.5-20.5"   34-52 cm	11.5-20"   29-51 cm	0°, 2°, 4°, 6°, 8°
Tubing Size	Weight Capacity	Ansi Resna WC-19 Transit			
1 3/8"   3.5 cm	200 lbs.   90 kg	Approved			